

XTRABOND®9500

MODIFIED POLYURETHANE SEALANT

XtraBond®9500 is a high performance, one component, permanently flexible, easy to use, multi-purpose fast cure modified polyurethane sealant. Xtrabond®9500 cures rapidly when exposed to atmospheric moisture to form a durable bond.

Features

- AAMA Certified
- Non-Yellowing
- Environmentally friendly
- No Solvents, Very Low VOCs
- Can Be Painted in 2 hours
- Fast Cure at a wide range of temperatures
- Aggressive Adhesion to common construction substrates
- Compatible with SBS Flashing

Applications

- Perimeter sealing of windows, doors & skylights
- Siding
- Construction Flashing Applications
- Sealing Waterproof Membrane
- Industrial Applications

INTERACTIVE
COLOR MATCHING
PROGRAM

NOW IN
300+
COLORS
XtraBond.com Color



Specifications

Skin Time	Less than 20 minutes @ 77 degF/ 50% RH
Tack Free Time	Less than 1 hour @ 77 degF / 50% RH
Cure Rate	1/4" Bead per 24 Hrs
VOC.....	9 g/L (0.0751 lb/gal)
Elongation @ Break	450%
Shore A	35 +/- 5
Movement Capability	25%
UV Rating	No discoloration or change in appearance after 2500 hrs of UV
Lap Shear	350 psi
Tensile Strength	250 psi
Staining	None
Low Temp. Flexibility	Retained to -90 deg. F.
High Temp. Flexibility	Up to 425 deg. F for short periods
Sag	None



XTRABOND®9500

MODIFIED POLYURETHANE SEALANT

COLOR BROCHURE



PREMIER
INDUSTRIAL SUPPLY



PREMIER
INDUSTRIAL SUPPLY

EMAIL & ONLINE:
INFO@PREMIERINDUSTRIAL.NET
WWW.PREMIERINDUSTRIAL.NET

WEST COAST:
23040 N 11TH AVE. STE 112
PHOENIX, AZ 85027
PH: 623-780-3160
FX: 623-478-2566

EAST COAST:
4282B STRAUSSER ST. NW
NORTH CANTON, OH 44720
PH: 330-244-2907
FX: 330-244-9423