

MATERIAL SAFETY DATA SHEET

PREMIER INDUSTRIAL SUPPLY, INC.

Product Name: XTRATAPE SOLID BUTYL GRIP TAPLE
Date Issued: March 3, 2009

1. Company Identification & Chemical Product

Product Brand Name: XtraTape
Product Use: Sealant & Adhesive
Proper DOT Shipping: Caulking & Glaziers, NOI
DOT Hazard Classification: NONE

Company Contact Information

Premier Industrial Supply, Inc.
23040 N.11th Ave Ste 112
Phoenix, AZ 85027

Emergency Telephone Number

CHEMTREC: 800-424-9300 (24 hours)
Telephone: 866-512-4583

2. Information on Ingredients

| <u>CHEMICAL NAME</u> | <u>CAS NUMBER</u> | <u>WEIGHT %</u> |
|----------------------------|-------------------|-----------------|
| Calcium Carbonate | 1317-65-3 | <32 |
| Talc | 14807-96-6 | <40 |
| Titanium Dioxide (white) | 13463-67-7 | <10 |
| Carbon Black (dark colors) | 1333-86-4 | <10 |

3. Hazards Identification

Emergency Overview

Tacky rubber based extrusion with very little odor
In case of fire, use foam, dry chemical, CO2

First Aid Measures

ROUTE OF ENTRY

Ingestion

SYMPTOMS OF EXPOSURE

Inhalation: N/A.

Eye Contact: Can cause eye irritation with direct contact. Symptoms include stinging, tearing, redness and swelling of eyes.

Skin Contact: A single short exposure can cause skin irritation or loss of natural oils. Symptoms may include redness and burning of skin

Ingestion: May cause gastrointestinal track irritation..

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

Eye or Skin Disease

CHRONIC EFFECTS

Over exposure to a component of this material has been suggested as a cause of liver abnormalities in laboratory animals.

CARCINOGEN: NONE

TERATOGENS: NONE

REPRODUCTIVE TOXINS: NONE

4. FIRST AID MEASURES

Inhalation: N/A

Eye Contact: Immediately flush eyes with copious amounts of water

Skin Contact: Immediately wash affected areas with large amounts of soap & water. Continue for 15 minutes. Get Medical attention if irritation develops.

Ingestion: Do not induce vomiting or give anything by mouth. Get immediate medical attention.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

On large fires use dry chemical, foam or water spray. On small fires use carbon dioxide, dry chemicals or water spray. Water can be utilized to cool containers exposed to fires.

SPECIAL FIREFIGHTIN INSTRUCTIONS

Thermal decomposition may produce toxic organic compounds. Avoid breathing smoke

6. ACCIDENTAL RELEASE MEASURES

Recover for reprocessing or disposal.

7. HANDLING AND STORAGE

Personal Pre Cautionary Measures: Avoid Breathing vapors in top of shipping containers. Keep containers closed & cool. Use with adequate ventilation. Avoid contact with skin and clothing. Wash thoroughly after handling. Observe all PPE Suggestions in section 8.

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

PERSONAL PROTECTIONS

Ventilation: Local and General Ventilation are recommended but not required

Respiratory Protection: Not normally needed

Eye Protection: Wear safety glasses with side shields as a minimum

Skin Protection: Impervious gloves are suggested. Wash at mealtimes and end of shift.

Gloves: Not normally needed

Clothes: Wear clothing that will protect the skin from exposure to this chemical.

EXPOSURE CONTROLS

| COMPONENTS | OSHA PEL | | ACGIH TLV | |
|-------------------|----------|------|-----------|------|
| | TWA | STEL | TWA | STEL |
| Titanium Dioxide | 15mg/m | N/E | 10 mg/m | N/E |
| Carbon Black | 3.5mg/m | N/E | 3.5 mg/m | N/E |
| Calcium Carbonate | 15mg/m | N/E | 10 mg/m | N/E |
| Talc | 5mg/m | N/E | 10 mg/m | N/E |

ENGINEERING CONTROLS

Use local exhaust or general dilution ventilation system.

9. PHYSICAL & CHEMICAL PROPERTIES

PH: N/A

Boiling Point: N/A

Vapor Density: Heavier Air

Odor: Mild

Color: N/A

Melting Point: 400

Water Solubility: Negligible

Freeze Point: N/A

State: Paste

Specific Gravity: - 1.48

Reactivity to Water: Incompatible

10. STABILITY AND REACTIVITY

INCOMPATIBILITIES:

Avoid contact with strong acids, caustic materials and oxidizers

REACTIVITY:

Stable

HAZARDOUS DECOMPOSITION PRODUCTS:

May form oxides of carbon and various unidentified organic compounds

CONDITIONS TO AVOID:

Avoid temperatures above 120 Degrees

11. TOXICOLOGICAL INFORMATION

FOR CARBON BLACK:

IARC- GROUP 2B (possibly carcinogenic to humans)

FOR PRODUCT:

Not Established

FOR TITANIMUM DIOXIDE:

Trochimowicz, et al.c J. Appl. Tox., 8, 383-385 (1988)

| | |
|---------------------|-------------------|
| Oral LD (rat) | >25g/kg |
| Dermal LD (rabbit) | >10 g/kg |
| Inhalation LC (rat) | >6.82 mg/l (4 hr) |

12. ECOLOGICAL INFORMATION

FOR PRODUCT

Not Established

13. DISPOSAL CONSIDERATIONS

RCRA WASTE CODE

Not Regulated. Observed all applicable federal, state, and local regulations.
Material is not classified as a hazardous waste per 40 CFR 261.

14. TRANSPORT INFORMATION

Marine Transport

None

DOT (usa):

Caulking & Glaziers, NOI

DOT Hazard Classification:

None

UN/NA Number:

Not Applicable

Label Required:

None

15. REGULATORY INFORMATION

OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200)

X Hazardous ___ Non- Hazardous

CERCLA/SUPERFUND (40 CFR 117, 302)

| CHEMICAL NAME | RQ (lbs)/(kg) |
|---------------|---------------|
| N/A | N/A |

SARA EXTREMELY HAZARDOUS SUBSTANCE (40 CFR 355)

| CHEMICAL NAME | TPQ (lbs) | RQ (lbs)/(kg) |
|---------------|-----------|---------------|
| N/A | N/A | N/A |

SARA TOXIC CHEMICALS (40 CFR 372)

| CHEMICAL NAME | CASE # | % |
|---------------|--------|-----|
| N/A | N/A | N/A |

SARA HAZARD CATEGORIES (40 CFR 370)

X Acute ___ Chronic ___ Fire ___ Pressure ___ Reactive

WORK PLACE HAZARDOUS MATERIAL INFORMATION SYSTEMS (CRP Section 33)

This product has been classified according to the hazard criteria of the Controlled Products Regulation and the MSDS contains all required information.

3 Controlled Product: Classification: D2B

___ Not Controlled Product

INVENTORY STATUS

The ingredients of this chemical are listed on the US TSCA Chemical Substance Inventory Substance Inventory.

TOXIC SUBSTANCE CONTROL ACT:

No specific regulation apply

STATE REGULATION

California Proposition 65

Crystalline Silicone Warning

This chemical is known to the State of California to cause cancer, birth defects and reproductive harm.

Massachusetts Right to Know List

Carbon Black, Titanium Dioxide

Pennsylvania Right to Know List

Carbon Black, Titanium Dioxide

New Jersey Right to Know List

Carbon Black , Titanium Dioxide

Minnesota Hazardous Substance List

Carbon Black , Titanium Dioxide

Rhode Island Hazardous Substance List

Carbon Black , Titanium Dioxide

16. OTHER INFORMATION

Disclaimer: The opinions expressed herein are those of qualified experts within Premier Industrial Supply Inc. We believe the information contained herein is current as the date of this MSDS. Since the use of the product is not within the control of Premier Industrial Supply Inc. it is the user's obligation to determine the conditions of safe use.

PREPARED BY: Premier Industrial Supply Inc.

MSDS #: XTRATAPE

DATE PREPARED: March 3, 2009

DATE ISSUED: March, 2009