

GLASS CLEANER

AMMONIA FREE AEROSOL FORMULA

Premier Industrial Supply, Inc. Glass Cleaner is an ozone friendly glass and surface cleaner formulated for the glass, windows and surface markets. It is an ammonia free, streak free, non-flammable, aerosol formula concentrate used to clean windshields, glass, metal, and other hard surfaces.



Features

- Ammonia free
- Streak free
- No evaporation or dilution
- User friendly
- Eliminates spots
- Removes films
- Dissolves grease, oil, finger prints and smudges
- CARB & VOC compliant

Applications

- Windows
- Mirrors
- Windshields
- Glass
- Ceramic flat surfaces



MADE IN THE U.S.A.



Proud Member



PREMIER
INDUSTRIAL SUPPLY
www.premierindustrial.net

866-512-GLUE
www.xtrabond.com

AMMONIA FREE AEROSOL FORMULA
GLASS CLEANER

GLASS CLEANER

AMMONIA FREE AEROSOL FORMULA

METHOD OF APPLICATION:

Shake well before each use. May not spray in colder weather conditions. Remove protective cap – Hold dispenser upright. Point valve opening toward window or glass to be sprayed, holding about 8 to 12 inches away. Press button - spray on fine mist and wipe surface clean. For best results, polish with a lint-free, cotton cloth.

PACKAGING:

19 oz. can, 12 cans per case.

LIMITATION:

Store in a cool, dry place. Do not place in hot water or near radiators, stoves or other sources of heat. Do not puncture, incinerate or store the container at temperatures over 120 F or in direct sunlight.

CAUTIONS: Avoid contact with eyes and skin. Intentional misuse by concentrating and inhaling the product can be harmful to liver and kidney.

FIRST AID: EYE: Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation develops or persists. **SKIN:**

Immediately flush skin with plenty of water. Get medical attention if irritation develops or persist. **INHALATION:** Move to fresh air. Call a physician if symptoms develop or persist. **INGESTION:** Have victim rinse mouth

thoroughly with water. Do not induce vomiting without medical advice. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration.

CONTAINS (CAS No.): Water (7732-18-5), 2- Butoxyethanol (111-76-2), Ethyl Alcohol (64-17-5), Methanol (67-56-1), n-Butane (106-97-8), and Propane (74-98-6).

WARNING:

Product is not required to be labeled as flammable as described in 16 CFR 1500.3 and 1500.45. Keep away from heat, sparks, and flames. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120 F (49 C) as container may burst. Avoid prolonged exposure to sunlight. Use with adequate ventilation.

KEEP OUT OF REACH OF CHILDREN.



SPRAY
CANS

XTRABOND

SEALANTS AND ADHESIVES



PREMIER
INDUSTRIAL SUPPLY

www.premierindustrial.net



Proud Member



866-512-GLUE

www.xtrabond.com

distributed by:

REV. 03/08 • SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE