

XTRABOND® 1500

RUBBER BUTYL SEALANT

XtraBond® 1500 is a one component, gun grade, permanently flexible, general purpose butyl rubber sealant. Manufactured for excellent adhesion to glass, wood, roof tile, concrete, clay, slate, sheet metal, most common building materials and most plastics without the need of a primer. XtraBond® 1500 has excellent weatherability, non staining, paintable and stays permanently elastic even when exposed to both high and low temperatures.

Features

- Window & Door Approved
- Non-Sag & Slump
- 50 Year Durability
- Permanently Flexible
- Non-Staining
- Paintable
- Excellent Adhesion to Many Materials

Applications


- Window & Door Applications
- Industrial Applications
- Residential Building Applications

Specifications

Tack Free	<24 Hours
Cure Rate	1/4 " Bead / 24 Hours
Elongation @ Break	900 %
Hardness (shore A)	10 +/- 5
Movement	+/- 25%
Staining	None
UV Resistance	Excellent
Service Temperature	-40 deg. F to 180 deg. F



**50 YR
DURABILITY**



**MADE IN
THE U.S.A.**



**PREMIER
INDUSTRIAL SUPPLY**
www.premierindustrial.net



866-512-GLUE
www.xtrabond.com

XTRABOND[®] 1500

R U B B E R B U T Y L S E A L A N T

SURFACE PREPARATIONS:

The substrate must be clean, dry, frost free, sound and free of any oils, greases or incompatible sealers, paints or coatings that may interfere with adhesion. Do not apply if surface is damp or contaminated. It is recommended to test all substrates prior to applications.

HOW TO USE:

For Best Results, make sure surface is clean, dry and free of oil or grease. Cut nozzle to desired bead size and puncture inner seal. Apply with a caulking gun forcing sealant onto the substrate, then tool if needed. Can be applied in warm or cold conditions. Clean excess material with mineral spirits or similar solvent. It is the user's responsibility to thoroughly test all proposed uses with any and/or all substrates.

COLORS:

WHITE, ALUMINUM STONE


Special colors upon request

PACKAGING:

10.1 fl oz cartridges: Fixed Tip Nozzles

20.2 oz fl oz. Sausage Packs

Other packaging available upon request



STORAGE LIFE:

Material is to be stored in a controlled environment below 75 deg. F. Use within 18 months from date of manufacture.

SPECIFICATIONS:

TT-S-001657 Type I

LIMITED LIFETIME WARRANTY

This product is guaranteed to give satisfactory performance if applied in accordance with the label directions. Liability to Premier Industrial Supply, Inc. (Premier) is limited to a full refund of the purchase price or product replacement if product is proven defective. Premier shall not be liable for loss or damage, whether direct, consequential or incidental. There are no other warranties expressed or implied including the implied warranty of merchantability or fitness for a particular purpose.

WARNING:

This product contains chemicals known to the state of California to cause cancer, birth defects and/or reproductive harm.

NOTICE:

Not offered in California as other than a roof tile adhesive/sealant.



PREMIER
INDUSTRIAL SUPPLY
www.premierindustrial.net

REV. 6/09 • SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

866-512-GLUE
www.xtrabond.com

distributed by: