

XTRABOND® 1500NS

NON-SKINNING BUTYL SEALANT

XtraBond®1500NS is a one component, permanently flexible, non-skinning butyl based sealant. Excellent adhesion to panels, wood and roofing materials. XtraBond®1500NS has excellent weatherability, non staining, paintable and stays permanently elastic even when exposed to both high and low temperatures conditions.

FEATURES

- Non-Skinning
- Permanently Pliable Formula
- Remains Flexible
- Moisture Resistant
- Non-Drying

APPLICATIONS

- Acoustical Applications
- Industrial Applications
- Walk in coolers
- Metal Insulated Panels
- Pipe Insulation
- Standing Seam Roof Panels

SPECIFICATIONS

Staining	None
UV Resistance	Excellent
Service Temperature	-40 deg. F to 180 deg. F
Sag	None
Flow / Slump	None
Extrudability	100g-115g/60sec
Blistering	None
Bleeding	None



TOLL-FREE **866-512-GLUE** (4583)
WWW.PREMIERINDUSTRIAL.NET



XTRABOND®1500NS

NON-SKINNING BUTYL SEALANT

ADDITIONAL APPLICATIONS:

XtraBond1500®NS is also compatible with the following materials and substrates: Kynar 500/Hylar 5000, Mica Fluoropon, Metallic Fluoropon and Weather X Siliconized Modified Polyester (SMP).

SURFACE PREPARATIONS:

The substrate must be clean, dry, frost free, sound and free of any oils, greases or incompatible sealers, paints or coatings that may interfere with adhesion. Do not apply if surface is damp or contaminated. It is recommended to test all substrates prior to applications.

HOW TO USE:


For Best Results, make sure surface is clean, dry and free of oil or grease. Cut nozzle to desired bead size and puncture inner seal. Apply with a caulking gun forcing sealant onto the substrate, then tool if needed. Can be applied in warm or cold conditions. Clean excess material with mineral spirits or similar solvent.

COLOR:

White and Aluminum Stone
Special colors upon request

PACKAGING:

- 10.1 fl oz cartridges: Fixed-Tip and Twist-On Nozzles
- 20.2 fl oz Sausage Packs
- Other packaging is available upon request.



STORAGE LIFE:

Material is to be stored under controlled dry environment (below 75 F). Use within 24 months from date of manufacture.

SPECIFICATIONS:

XtraBond®1500NS conforms to the requirements of Federal Specifications -TT-S-001657 type I. Conforms to CAN/CGSB 19.21 M87.

WARNING:

This product contains chemicals known to the state of California to cause cancer, birth defects and/or reproductive harm.

PLEASE RECYCLE

Premier Industrial Supply, Inc. is committed to caring for the environment and adheres to nationally recognized standards for "green" manufacturer. Our product meets VOC emission standards, and our tubes are made with post-recycled plastic material. We ask that you do your part and recycle the empty cartridges when done.

LIMITED LIFETIME WARRANTY

This product is guaranteed to give satisfactory performance if applied in accordance with the label directions. Liability to Premier Industrial Supply, Inc. (Premier) is limited to a full refund of the purchase price or product replacement if product is proven defective. Premier shall not be liable for loss or damage, whether direct, consequential or incidental. There are no other warranties expressed or implied including the implied warranty of merchantability or fitness for a particular purpose.



EMAIL & ONLINE:
INFO@PREMIERINDUSTRIAL.NET
WWW.PREMIERINDUSTRIAL.NET

WEST COAST:
23040 N 11TH AVE. STE 112
PHOENIX, AZ 85027
PH: 623-780-3160
FX: 623-478-2566

EAST COAST:
4282B STRAUSSER ST. NW
NORTH CANTON, OH 44720
PH: 330-244-2907
FX: 330-244-9423

SPECIFICATIONS SUBJECT TO
CHANGE WITHOUT NOTICE