

XTRABOND™ 150

RTV MILDEW RESISTANT SILICONE SEALANT

XtraBond™ 150 is a one component, permanently flexible, RTV Mildew resistant silicone sealant. Manufactured for excellent adhesion to cultured marble, tile, glass, vinyl, aluminum, and sheet metal without the need of a primer. XtraBond™ 150 cures rapidly when exposed to atmospheric moisture to form a durable tight bond.



Features

- Approved for FDA & USDA Requirements
- Approved for Cultured Marble
- Excellent adhesion to Glass
- Window & Door Approved
- Non-Sag & Slump
- 50 Year Durability
- Quick Curing
- Consistent Gunability & Tooling

Applications

- Cultured Marble Applications
- Window & Door Applications
- Glass Replacement
- Kitchen & Bath
- Industrial Applications

Specifications

| | |
|---|--------------------------|
| Skin Time | 12 Minutes |
| Tack Free Time | 20 Minutes |
| Cure Rate | 1/4 " Bead / 24 Hours |
| VOC | 3.47 % |
| Elongation @ Break | 550 % |
| Hardness (shore A) | 20 +/- 5 |
| Movement | +/- 25% |
| Peel Strength | 19 psi |
| Bond Durability on Glass/Vinyl/Alumimum... | 25% |
| Tensile Strength..... | 375 psi |
| Staining | None |
| UV Resistance | Excellent |
| Service Temperature | -40 deg. F to 450 deg. F |



866-512-GLUE
www.xtrabond.com



XTRABOND™ 150

RTV MILDEW RESISTANT SILICONE SEALANT

SURFACE PREPARATIONS:

The substrate must be clean, dry, frost free, sound and free of any oils, greases or incompatible sealers, paints or coatings that may interfere with adhesion. Do not apply if surface is damp or contaminated. It is recommended to test all substrates prior to applications.

HOW TO USE:


For Best Results, ensure surface is clean, dry and free of oil or grease. Cut nozzle to desired bead size and puncture inner seal. Apply with a caulking gun forcing sealant onto the substrate, then tool if needed. Sealant will gain a skin in 12 minutes and exhibit full cure within 24 hours. Can be applied in warm or cold conditions. Clean excess material with mineral spirits or similar solvent. It is the user's responsibility to thoroughly test any proposed uses with any and/or all substrates.

COLOR:

Almond, Aluminum Stone, Beige, Black, Bronze, Clear, Desert Tan, Translucent, White

PACKAGING:

10.1 fl oz cartridges: Fixed-Tip and Twist-On Nozzles
29 oz quarts
Other packaging is available upon request.



STORAGE LIFE:

Material is to be stored under controlled dry environment (below 75 deg. F.) Use within 18 months from date of manufacture.

SPECIFICATIONS:

ASTM C-920, Type S, Grade NS, Class 25, Use NT, M, G, A, O; TT-S-00230C & TT-S-001534A (COM-NBS).

Xtrabond 150 meets performance requirements for the following: FDA/ USDA requirements for use in establishments operating under Federal Meat and Poultry Inspection Program. When cured and washed, ingredients remaining or which could migrate to food are listed on FDA Regulation No. 21 CFR 177.2600. Meets Federal Specifications TTS-00230C, ASTM C-920 and NSF Standard 51.

LIMITED LIFETIME WARRANTY

This product is guaranteed to give satisfactory performance if applied in accordance with the label directions. Liability to Premier Industrial Supply, Inc. (Premier) is limited to a full refund of the purchase price or product replacement if product is proven defective. Premier shall not be liable for loss or damage, whether direct, consequential or incidental. There are no other warranties expressed or implied including the implied warranty of merchantability or fitness for a particular purpose.

WARNING:

This product contains chemicals known to the state of California to cause cancer, birth defects and/or reproductive harm.



PREMIER
INDUSTRIAL SUPPLY
www.premierindustrial.net

REV. 7/07 • SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

866-512-GLUE
www.xtrabond.com

distributed by: