

XTRABOND[®]25

ACRYLIC LATEX SEALANT

XtraBond[®]25 is a Premium Grade Multi-Purpose Acrylic Latex Sealant formulated to provide excellent adhesion and durability to a wide variety of interior and exterior substrates. XtraBond[®]25 has been specially developed for the installation of windows and doors.

FEATURES

- Water Clean Up
- Easy Gunning & Tooling
- Excellent Paintability
- Environmentally friendly
- Contains very low VOC
- Paintable in 2 hours*

APPLICATIONS

- Perimeter sealing of windows, doors & skylights
- Siding
- Lath & Plastering Penetrations
- Industrial Applications
- Interior Joint Movement Applications

SPECIFICATIONS

Skin Time	Less than 60 minutes @ 77 degF / 50% RH
Tack Free Time	Less than 30 minutes @ 77 degF / 50% RH
Elongation @ Break	150%
Shore A	35 +/- 5
Movement Capability	150%
UV Rating	No discoloration or change in appearance after 500 hours of UV
Lap Shear	125 psi
Tensile Strength	150 psi
Staining	None
Low Temp. Flexibility	Retained to 0 deg. F.
High Temp. Flexibility	Up to 120 deg. F for short periods
Sag	None



Proud Member

TOLL-FREE **866-512-GLUE** (4583)
WWW.PREMIERINDUSTRIAL.NET



XTRABOND[®]25

ACRYLIC LATEX SEALANT

HOW TO USE:

For best results, prepare clean, dry surface. Cut nozzle to desired bead size and puncture inner seal. Apply with a caulking gun, forcing sealant onto the substrate, then tool if needed. Bead can be painted within 2 hours depending upon bead size. Clean excess material with water. It is the user's responsibility to thoroughly test any proposed uses with any and/or all substrates.

COLORS:


White

PACKAGING:

- 10.1 fl oz plastic twist-on nozzle cartridges

STORAGE:

Material is to be stored under controlled dry environment (below 75 deg. F.) Use within 12 months from date of manufacture.



CAUTION

Uncured material may cause skin, eye, and respiratory system irritation. Use only in well ventilated area. In cases of eye contact or irritation, flush eyes immediately with running water for 15 minutes and obtain medical attention. For further health and safety information, consult the current Material Safety Data Sheet. For medical emergency, call Chemtrec at 1-800-424-9300. **KEEP AWAY FROM CHILDREN.** For Professional use only.

RECYCLE, PLEASE

Premier Industrial Supply, Inc. is committed to caring for the environment and adheres to nationally recognized standards for "green" manufacturer. Our product meets VOC emission standards, and our tubes are made with post-recycled plastic material. We ask that you do your part and recycle the empty cartridges when done.

LIMITED LIFETIME WARRANTY

This product is guaranteed to give satisfactory performance if applied in accordance with the label directions. Liability to Premier Industrial Supply, Inc. (Premier) is limited to a full refund of the purchase price or product replacement if product is proven defective. Premier shall not be liable for loss or damage, whether direct, consequential or incidental. There are no other warranties expressed or implied including the implied warranty of merchantability or fitness for a particular purpose.

XTRABOND
SEALANTS AND ADHESIVES



PREMIER
INDUSTRIAL SUPPLY

EMAIL & ONLINE:
INFO@PREMIERINDUSTRIAL.NET
WWW.PREMIERINDUSTRIAL.NET

WEST COAST:
23040 N 11TH AVE. STE 112
PHOENIX, AZ 85027
PH: 623-780-3160
FX: 623-478-2566

EAST COAST:
4282B STRAUSSER ST. NW
NORTH CANTON, OH 44720
PH: 330-244-2907
FX: 330-244-9423

SPECIFICATIONS SUBJECT TO
CHANGE WITHOUT NOTICE