

XTRABOND[®]350

LOW MODULUS NEUTRAL CURE SILICONE

XtraBond[®]350 is a one component, low modulus, 100% high performance alkoxy cure silicone sealant that cures in atmospheric moisture. Manufactured for excellent adhesion to vinyl, glass, aluminum, wood, sheet metal and most common building materials without the need of a primer. XtraBond[®]350 cures rapidly to form a durable tight bond.



FEATURES

- Indoor/Outdoor Use
- Low Odor
- Approved for Windows & Doors
- Excellent Flexibility
- Watertight
- Excellent Adhesion to Glass
- Mildew Resistant

APPLICATIONS

- Window Perimeters
- Industrial Applications
- Residential Applications

SPECIFICATIONS

Skin Time	8 minutes
Tack Free Time	18 minutes
Cure Rate	1/4" Bead per 24 Hrs
Specific Gravity	1.03
Elongation @ Break	400%
Hardness (Shore A)	23 +/- 5
Movement Capability	+/- 25%
Peel Strength	29 psi
Bond Durability on Glass/Vinyl/Aluminum	25%
Tensile Strength	275 psi
Staining	None
UV Resistance	Excellent
Service Temperature	-30 deg.F to 450deg.F



TOLL-FREE **866-512-GLUE** (4583)
WWW.PREMIERINDUSTRIAL.NET



XTRABOND[®]350

LOW MODULUS NEUTRAL CURE SILICONE

DIRECTIONS:

For Best Results, make sure surface is clean, dry and free of oil or grease. Cut tip of threaded end of cartridge. Thread nozzle on, and cut nozzle to desired beadsizes. Apply with a caulking gun forcing sealant onto the substrate, then tool if needed. Sealant will gain a skin in 10 minutes and exhibit full cure within 24 hours. Can be applied in warm or cold conditions. Clean excess material with mineral spirits or similar solvent.

COLORS:


This product is offered in hundreds of colors using our Custom Color Matching & Mixing System. For current color offerings, please visit the Online Color Matching Program:

www.premierindustrialsupply.net/color/

Custom Colors & Private Labeling available upon request.

PACKAGING:

- 10.1 fl oz plastic twist-on nozzle cartridges
- 10.3 oz & 20 oz fl oz. Sausages
- 1, 3, 5 & 55 gallon available upon request.



STORAGE:

Material is to be stored under controlled dry environment (below 90 F). Use within 24 months from date of manufacture. For best results, keep material in tightly closed containers when not in use.

CAUTION

Uncured material may cause skin, eye, and respiratory system irritation. Use only in well ventilated area. In cases of eye contact or irritation, flush eyes immediately with running water for 15 minutes and obtain medical attention. For further health and safety information, consult the current Material Safety Data Sheet. For medical emergency, call Chemtrec at 1-800-424-9300. **KEEP AWAY FROM CHILDREN.** For Professional use only.

RECYCLE, PLEASE

Premier Industrial Supply, Inc. is committed to caring for the environment and adheres to nationally recognized standards for "green" manufacturer. Our product meets VOC emission standards, and our tubes are made with post-recycled plastic material. We ask that you do your part and recycle the empty cartridges when done.

LIMITED LIFETIME WARRANTY

This product is guaranteed to give satisfactory performance if applied in accordance with the label directions. Liability to Premier Industrial Supply, Inc. (Premier) is limited to a full refund of the purchase price or product replacement if product is proven defective. Premier shall not be liable for loss or damage, whether direct, consequential or incidental. There are no other warranties expressed or implied including the implied warranty of merchantability or fitness for a particular purpose.



EMAIL & ONLINE:
INFO@PREMIERINDUSTRIAL.NET
WWW.PREMIERINDUSTRIAL.NET

SPECIFICATIONS SUBJECT TO
CHANGE WITHOUT NOTICE

WEST COAST:
23040 N 11TH AVE. STE 112
PHOENIX, AZ 85027
PH: 623-780-3160
FX: 623-478-2566

EAST COAST:
4282B STRAUSSER ST. NW
NORTH CANTON, OH 44720
PH: 330-244-2907
FX: 330-244-9423

SEALANTS AND ADHESIVES

XTRABOND