

XTRABOND™ 450

NEUTRAL CURE SILICONE SEALANT

XtraBond™ 450 is a one component, non sag, permanently flexible neutral cure silicone sealant. Manufactured for excellent adhesion to vinyl, glass, aluminum, wood, sheet metal and most common building materials without the need of a primer. XtraBond™ 450 cures rapidly when exposed to atmospheric moisture to form a durable tight bond.

Features

- AAMA Approved
- Excellent Adhesion to Glass
- Window & Door Approved
- Non-Sag & Slump
- 75 Year Durability
- Quick Curing
- Excellent UV Resistance
- Non-Yellowing
- Consistent Gunability & Tooling

Applications

- Window & Door Applications
- Glass Replacement
- Industrial Applications
- Copper Sheet Metal Applications

Specifications

Skin Time	10 Minutes
Tack Free Time	20 Minutes
Cure Rate	1/4 " Bead / 24 Hours
VOC	3. 27 %
Elongation @ Break	550 %
Hardness (shore A)-	25 +/- 5
Movement.....	+/- 25%
Peel Strength	19 psi
Bond Durability on	
Glass/Vinyl/Alumimum...	25%
Tensile Strength.....	255 psi
Staining	None
UV Resistance	Excellent
Service Temperature	-40 deg. F to 350 deg.



Manufacturer of
Verified Components



PREMIER
INDUSTRIAL SUPPLY
www.premierindustrial.net

866-512-GLUE
www.xtrabond.com