

XTRABOND[®]50S

SANDED PREMIUM GRADE SILICONIZED LATEX SEALANT

XtraBond[®]50S is a Premium siliconized acrylic sanded color caulk used for caulking and sealing corners, edges and joints in tile, counters or granite surfaces. Use XtraBond[®]50S caulking countertops and around sinks, bathtubs and backsplashes. Meets ASTM C834 standards for exterior grade caulks.

FEATURES

- Sanded Appearance
- Plethora of Colors
- Mold & Mildew Resistant
- Flexible
- Paintable with latex paint after full cure.
- Interior/Exterior Use

APPLICATIONS

- Tile & Flooring
- Cultured Marble
- Stucco Homes & Structures
- Masonry Applications

SPECIFICATIONS

Skin Time	Less than 15 minutes @ 77 degF/ 50% RH
Tack Free Time	Less than 1 hour @ 77 degF / 50% RH
Cure Rate	1/4" Bead per 24 Hrs
VOC.....	9 g/L 0.0751 lb/gal
Elongation @ Break	400%
Shore A	25 +/- 5
Movement Capability	25%
Lap Shear	550 psi
Staining	None
Low Temp. Flexibility	Retained to -90 deg. F.
High Temp. Flexibility	Up to 425 deg. F for short periods
Sag	None



Proud Member

TOLL-FREE **866-512-GLUE** (4583)
WWW.PREMIERINDUSTRIAL.NET



XTRABOND[®] 50S

SANDED PREMIUM GRADE SILICONIZED LATEX SEALANT

LIMITATIONS:

- Do not apply at temperatures below 40°F or above 105°F.
- Not for use on shower floors or pans, in steam rooms, in steam showers, swimming pools, or any place that will receive standing water or extreme high humidity.
- The caulk can stain other surfaces such as paint and wall paper, so mask these areas prior to caulk application.
- If sealing grout, mask over the caulk first.

SURFACE PREPARATIONS:

Surfaces should be clean and dry. Remove all loose particles, dirt, and old caulk. Ceramic surfaces should be free of soap film and hard water stains.

APPLICATION:

1. Trim tip to desired bead size.
2. Load into caulk gun.
3. Apply bead along seam, toward you.
4. Smooth with wet finger or putty knife.
5. Clean off any excess caulk with wet cloth immediately.

Color match is complete when caulk is fully cured. Wet sealant will appear lighter in color.

CLEAN-UP:

Clean tools, hands, and excess material immediately with warm soapy water or mineral spirits. Unused portion of Caulk should be capped and stored in a cool dry place.

PROTECTION:

Allow to set 48 hours prior to water or extreme humidity exposure. Higher humidity and cooler temperatures will extend cure time.

COLORS:

See our separate Color Chart offering over 275+ colors or visit:

www.premierindustrialsupply.net/color/


Custom Colors & Private Labeling available upon request.

PACKAGING:

- 10.1 fl oz plastic twist-on nozzle cartridges
- 1, 3, 5 & 55 gallon available upon request.

STORAGE LIFE:

12 months shelf life. Material is to be stored in a controlled environment below 75 deg. F.



LIMITED LIFETIME WARRANTY

This product is guaranteed to give satisfactory performance if applied in accordance with the label directions. Liability to Premier Industrial Supply, Inc. (Premier) is limited to a full refund of the purchase price or product replacement if product is proven defective. Premier shall not be liable for loss or damage, whether direct, consequential or incidental. There are no other warranties expressed or implied including the implied warranty of merchantability or fitness for a particular purpose.



EMAIL & ONLINE:
INFO@PREMIERINDUSTRIAL.NET
WWW.PREMIERINDUSTRIAL.NET

WEST COAST:
23040 N 11TH AVE. STE 112
PHOENIX, AZ 85027
PH: 623-780-3160
FX: 623-478-2566

EAST COAST:
4282B STRAUSSER ST. NW
NORTH CANTON, OH 44720
PH: 330-244-2907
FX: 330-244-9423

SPECIFICATIONS SUBJECT TO
CHANGE WITHOUT NOTICE