

XTRABOND™ 6500SC

MODIFIED NEOPRENE SEALANT - SURFACE COAT

XtraBond™ 6500SC Modified Neoprene Sealant Surface Coat is a high performance, one component, easy to apply surface coating. XtraBond™ 6500 SC is approved for moisture driven markets and the product has been specifically designed for the truck, trailer and container markets to assure a waterproof surface coat & patch.

Features

- Approved for Moisture & Damp Conditions
- Fast Cure
- High Strength Bond
- Excellent Adhesion to many Materials

Applications

- Truck and Trailer Roof Patch Applications
- Industrial Coating Applications
- Vertical & Horizontal Joint Surfaces
- Water Prevention in Container Use
- Roof Repair Applications

Specifications

Skin Time.....	Less than 10 minutes @ 77 degF/ 50% RH
Tack Free Time	Less than 1 hour @ 77 degF / 50% RH
Cure Rate	1/8" Bead per 24 Hrs
Elongation @ Break.....	400%
Shore A.....	60 +- 5
Adhesion-n-Peel.....	36pli
UV Rating	No discoloration or change in appearance after 2000 hours of UV
Staining	None
Low Temp. Flexibility	Retained to -75 degrees
High Temp. Flexibility	Up to 400 F for short periods
Sag	Self-Leveling
Service Temperature	-30 deg F - 150 deg F.



866-512-GLUE
www.xtrabond.com



XTRABOND™ 6500SC

MODIFIED NEOPRENE SEALANT - SURFACE COAT

HOW TO USE:

For best results, prepare clean, dry surface. Clean excess material with mineral spirits or similar solvents. It is the user's responsibility to thoroughly test any proposed uses with any and/or all substrates.

COLOR:

Aluminum Stone, Special colors upon request

PACKAGING:

1 gallon containers

5 gallon pails

55 gallon drums



PAILS &
DRUMS

STORAGE LIFE:

6 month shelf life. Material is to be stored in a controlled environment below 75 deg. F.

PRECAUTIONS:

Flammable material, contains xylene. Use only in well ventilated areas. Keep away from heat, sparks, or flames. Avoid contact with eyes or skin. If swallowed, do not induce vomiting, call a physician. Refer to MSDS for additional information. KEEP OUT OF REACH OF CHILDREN.



LIMITED LIFETIME WARRANTY

This product is guaranteed to give satisfactory performance if applied in accordance with the label directions. Liability to Premier Industrial Supply, Inc. (Premier) is limited to a full refund of the purchase price or product replacement if product is proven defective. Premier shall not be liable for loss or damage, whether direct, consequential or incidental. There are no other warranties expressed or implied including the implied warranty of merchantability or fitness for a particular purpose.

WARNING:

This product contains chemicals known to the state of California to cause cancer, birth defects and/or reproductive harm.



PREMIER
INDUSTRIAL SUPPLY
www.premierindustrial.net

REV. 1/07 • SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

866-512-GLUE
www.xtrabond.com

distributed by: