

XTRABOND® 7500TX

FAST CURING TEXTURED POLYURETHANE SEALANT

XtraBond® 7500TX is a textured, one component, high performance, permanently flexible, easy to use, multi-purpose fast cure polyurethane sealant. XtraBond® 7500TX cures rapidly when exposed to atmospheric moisture to form a durable bond.

Features


- Textured Appearance
- Contains very low VOC
- Prop. 65 Compliant
- Fast Cure at a wide range of temperatures
- Aggressive Adhesion to common construction substrates
- Paintable & Sandable
- Superior Adhesion to many Residential Construction & Building Materials

Applications

- Perimeter sealing of windows, doors & skylights
- Lathing and Stucco Applications
- Construction Flashing Applications
- Sealing Waterproof Membrane
- Industrial Applications

Specifications

Tack Free Time	Less than an 4 hours @ 77 F / 50% RH
Skin Time	Less than 1.5 Hours @ 77 F/ 50% RH
Cure Rate	¼" Bead/24 hours
VOC	3.59%
Elongation @ Break	525%
Shore A	30 + 5
Movement Capability %	25%
Peel Strength	30 psi
Lap Shear	325 psi
Tensile Strength	250 psi
Staining	None
Service Temperature	185 deg. F



**MADE IN
THE U.S.A.**



**PREMIER
INDUSTRIAL SUPPLY**
www.premierindustrial.net



866-512-GLUE
www.xtrabond.com

XTRABOND[®]7500TX

FAST CURING TEXTURED POLYURETHANE SEALANT

SURFACE PREPARATIONS:

The substrate must be clean, dry, frost free, sound and free of any oils, greases or incompatible sealers, paints or coatings that may interfere with adhesion. Do not apply if surface is damp or contaminated. It is recommended to test all substrates prior to applications.

HOW TO USE:


For best results, prepare a clean, dry surface. Cut nozzle to desired bead size and puncture inner seal. Apply with a caulking gun forcing sealant onto the substrate, then tool if needed. Clean excess material with mineral spirits or similar solvents. It is the user's responsibility to thoroughly test an proposed uses with any and/or all substrates.

PACKAGING:

10.1 fl oz cartridges: Fixed-Tip Nozzles

20 oz fl oz. sausages

1, 3, 5 & 55 gallon pails/drums available upon request.



STORAGE LIFE:

12 month shelf life. Material is to be stored in a controlled environment below 75 deg. F.

SPECIFICATIONS:

ASTM C-920 Type S & TTS-0230C, Grade NT, Class 25. AAMA 808.3-92 Exterior Perimeter Sealing.

LIMITED LIFETIME WARRANTY

This product is guaranteed to give satisfactory performance if applied in accordance with the label directions. Liability to Premier Industrial Supply, Inc. (Premier) is limited to a full refund of the purchase price or product replacement if product is proven defective. Premier shall not be liable for loss or damage, whether direct, consequential or incidental. There are no other warranties expressed or implied including the implied warranty of merchantability or fitness for a particular purpose.

XTRABOND
SEALANTS AND ADHESIVES



PREMIER
INDUSTRIAL SUPPLY
www.premierindustrial.net

REV. 6/09 • SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

866-512-GLUE
www.xtrabond.com

distributed by: