

# XTRABOND™ 9500SC

## MODIFIED POLYURETHANE SEALANT - SURFACE COAT

XtraBond 9500SC Modified Polyurethane Sealant Surface Coat is a high performance, one component, easy to apply surface coating. XtraBond 9500 SC is approved for moisture driven markets and the product has been specifically designed for the truck, trailer and container markets to assure a waterproof surface coat & patch.

### Features

- Approved for Moisture & Damp Conditions
- Fast Cure
- High Strength Bond
- Advance Formulation
- No Solvents
- No Shrinkage
- Odorless

### Applications

- Truck and Trailer Roof Patch Applications
- Industrial Coating Applications
- Vertical & Horizontal Joint Surfaces
- Water Prevention in Container Use
- Roof Repair Applications

### Specifications

Skin Time.....	Less than 30 minutes @ 77 degF/ 50% RH
Tack Free Time .....	Less than 1 hour @ 77 degF / 50% RH
Cure Rate .....	1/8" Bead per 24 Hrs
VOC .....	10 g/L (0.0751 lb/gal)
Elongation @ Break.....	150%
Shore A .....	40 + 5
Adhesion-n-Peel.....	36pli
UV Rating .....	No discoloration or change in appearance after 2000 hours of UV
Lap Shear .....	210 psi
Tensile Strength .....	175 psi
Staining .....	None
Low Temp. Flexibility .....	Retained to -75 degrees
High Temp. Flexibility .....	Up to 400 F for short periods
Sag .....	Self-Leveling



**866-512-GLUE**  
[www.xtrabond.com](http://www.xtrabond.com)



# XTRABOND™ 9500SC

## MODIFIED POLYURETHANE SEALANT - SURFACE COAT

### HOW TO USE:

For best results, prepare clean, dry surface. Clean excess material with mineral spirits or similar solvents. It is the user's responsibility to thoroughly test any proposed uses with any and/or all substrates.

### COLOR:

Aluminum Stone, Special colors upon request

### PACKAGING:

1 gallon containers  
5 gallon pails  
55 gallon drums

### STORAGE LIFE:

6 months shelf life. Material is to be stored in a controlled environment below 75 degrees

### LIMITED LIFETIME WARRANTY

This product is guaranteed to give satisfactory performance if applied in accordance with the label directions. Liability to Premier Industrial Supply, Inc. (Premier) is limited to a full refund of the purchase price or product replacement if product is proven defective. Premier shall not be liable for loss or damage, whether direct, consequential or incidental. There are no other warranties expressed or implied including the implied warranty of merchantability or fitness for a particular purpose.

### WARNING:

This product contains chemicals known to the state of California to cause cancer, birth defects and/or reproductive harm.



**PREMIER**  
**INDUSTRIAL SUPPLY**  
[www.premierindustrial.net](http://www.premierindustrial.net)

REV. 12/06 • SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

**866-512-GLUE**  
[www.xtrabond.com](http://www.xtrabond.com)

distributed by: