

XTRABOND®9500SL

SELF-LEVELING MODIFIED POLYURETHANE SEALANT

XtraBond®9500SL is a high performance, self-leveling, one component, permanently flexible, easy to use, multi-purpose fast cure modified polyurethane sealant. XtraBond®9500 cures rapidly when exposed to atmospheric moisture to form a durable bond.

FEATURES

- Self-Leveling
- Non-Yellowing
- Environmentally friendly
- No Solvents, Very Low VOCs
- Can Be Painted in 2 hours
- Fast Cure at a wide range of temperatures

APPLICATIONS

- Transportation Industry
- Industrial Applications
- Roof Joint Seals
- Self Leveling Properties



SPECIFICATIONS

Skin Time	Less than 20 minutes @ 77 degF/ 50% RH
Tack Free Time	Less than 1 hour @ 77 degF / 50% RH
Cure Rate	1/4" Bead per 24 Hrs
VOC.....	9 g/L (0.0751 lb/gal)
Elongation @ Break	450%
Shore A	35 +- 5
Movement Capability % ..	25%
UV Rating	No discoloration or change in appearance after 2500 hours of UV
Lap Shear	325 psi
Tensile Strength	250 psi
Staining	None
Low Temp. Flexibility	Retained to -90 degrees
High Temp. Flexibility	Up to 425 deg. F for short periods



Proud Member

TOLL-FREE **866-512-GLUE** (4583)
WWW.PREMIERINDUSTRIAL.NET



XTRABOND® 9500SL

SELF-LEVELING MODIFIED POLYURETHANE SEALANT

HOW TO USE:

For best results, prepare clean, dry surface. Cut nozzle to desired bead size and puncture inner seal. Apply with a caulking gun forcing sealant onto the substrate, then tool if needed. Can be painted within 2 hours depending upon bead size. Clean excess material with mineral spirits or similar solvents. It is the user's responsibility to thoroughly test any proposed uses with any and/or all substrates.

SURFACE PREPARATIONS:

The substrate must be clean, dry, frost free, sound and free of any oils, greases or incompatible sealers, paints or coatings that may interfere with adhesion. Do not apply if surface is damp or contaminated. It is recommended to test all substrates prior to applications.

COLOR:

ALUMINUM STONE

Special colors upon request

PACKAGING:

10.1 fl oz plastic fixed nozzle cartridges
1, 3, 5 & 55 gallon available upon request.

STORAGE LIFE:

10 months shelf life. Material is to be stored in a controlled environment below 75 degrees

SPECIFICATIONS:

ASTM C-920 Type S & TTS-0230C, Grade NT, Class 25.

WARNING:

This product contains chemicals known to the state of California to cause cancer, birth defects and/or reproductive harm.

XTRABOND
SEALANTS AND ADHESIVES

LIMITED LIFETIME WARRANTY

This product is guaranteed to give satisfactory performance if applied in accordance with the label directions. Liability to Premier Industrial Supply, Inc. (Premier) is limited to a full refund of the purchase price or product replacement if product is proven defective. Premier shall not be liable for loss or damage, whether direct, consequential or incidental. There are no other warranties expressed or implied including the implied warranty of merchantability or fitness for a particular purpose.



REV. 2/09 SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

866-512-GLUE
www.xtrabond.com

distributed by: