

# XTRABOND®9500HS

## HIGH STRENGTH POLYMER ADHESIVE/SEALANT

XtraBond®9500HS is a one component, permanently flexible, multiple purpose easy to use fast cure high strength adhesive/sealant. XtraBond®9500HS is environmentally friendly and offers excellent adhesion to vinyl, sheet metal, steel, prepainted metals, wood, glass, aluminum, plastic, common construction substrates of: window, door, siding, flashing & underlayment papers. Sealant does not contain any solvents or isocyanates and typically applied without the need of any primer. XtraBond®9500HS has excellent weatherability, non yellowing, non staining, paintable, and stays permanently elastic.



### FEATURES

- Non-yellowing
- Paintable
- No Solvents
- Voc Compliant

### APPLICATIONS

- Metal Building
- Metal Roofing
- Wall Panels
- Industrial Applications
- Recreational Vehicles
- Tractor Trailers & Buses

### SPECIFICATIONS

Skin Time .....	15 minutes @ 77 degF/ 50% RH
Tack Free Time .....	40 minutes @ 77 degF / 50% RH
Cure Rate .....	1/4" Bead per 24 Hrs
VOC.....	6 g/L (0.05 lb/gal)
Elongation @ Break .....	300%
Shore A .....	45%
Movement Capability .....	25%
UV Rating .....	No discoloration or change in appearance after 2500 hrs of UV
Lap Shear .....	395 psi
Tensile Strength .....	485 psi
Staining .....	None
Low Temp. Flexibility .....	Retained to -90 deg. F.
High Temp. Flexibility .....	Up to 425 deg. F for short periods
Sag .....	None



TOLL-FREE **866-512-GLUE** (4583)  
WWW.PREMIERINDUSTRIAL.NET



# XTRABOND® 9500HS

## HIGH STRENGTH POLYMER ADHESIVE/SEALANT

### HOW TO USE:

For best results, prepare clean, dry surface. Cut nozzle to desired bead size and puncture inner seal. Apply with a caulking gun forcing sealant onto the substrate, then tool if needed. Can be painted within 2 hours depending upon bead size. Clean excess material with mineral spirits or similar solvents. It is the user's responsibility to thoroughly test any proposed uses with any and/or all substrates.

### SURFACE PREPARATIONS:

For Best Results, make sure surface is clean, dry and free of oil or grease. Cut nozzle to desired bead size and puncture inner seal. Apply with a caulking gun forcing sealant onto the substrate, then tool if needed. Can be applied in warm or cold conditions. Clean excess material with mineral spirits or similar solvent.

### COLOR:


This product is offered in hundreds of colors using our Custom Color Matching & Mixing System. For current color offerings, please visit the Online Color Matching Program:

[www.premierindustrialsupply.net/color/](http://www.premierindustrialsupply.net/color/)

Custom Colors & Private Labeling available upon request.

### PACKAGING:

- 10.1 fl oz plastic twist-on nozzle cartridges
- 10.3 oz & 20 oz fl oz. Sausages
- 1, 3, 5 & 55 gallon available upon request.



### STORAGE LIFE:

Material is to be stored under controlled dry environment (below 75 F). Use within 10 months from date of manufacture for sausage and cartridge, and 6 months for drums.

### SPECIFICATIONS:

Exceeds the requirements of ASTM C 920, Type S, Grade NS, Class 25, Use NT, M, G and A • Federal Specification TT-S-00230C, Type II, Class A • CAN/CGSB-19 13-M87 • AAMA 808.3-92 Exterior Perimeter Sealing.

### PLEASE RECYCLE

Premier Industrial Supply, Inc. is committed to caring for the environment and adheres to nationally recognized standards for "green" manufacturer. Our product meets VOC emission standards, and our tubes are made with post-recycled plastic material. We ask that you do your part and recycle the empty cartridges when done.

### LIMITED LIFETIME WARRANTY

This product is guaranteed to give satisfactory performance if applied in accordance with the label directions. Liability to Premier Industrial Supply, Inc. (Premier) is limited to a full refund of the purchase price or product replacement if product is proven defective. Premier shall not be liable for loss or damage, whether direct, consequential or incidental. There are no other warranties expressed or implied including the implied warranty of merchantability or fitness for a particular purpose.



EMAIL & ONLINE:  
[INFO@PREMIERINDUSTRIAL.NET](mailto:INFO@PREMIERINDUSTRIAL.NET)  
[WWW.PREMIERINDUSTRIAL.NET](http://WWW.PREMIERINDUSTRIAL.NET)

WEST COAST:  
23040 N 11<sup>TH</sup> AVE. STE 112  
PHOENIX, AZ 85027  
PH: 623-780-3160  
FX: 623-478-2566

EAST COAST:  
4282B STRAUSSER ST. NW  
NORTH CANTON, OH 44720  
PH: 330-244-2907  
FX: 330-244-9423

SPECIFICATIONS SUBJECT TO  
CHANGE WITHOUT NOTICE