

# XTRABOND™ 9500

## MODIFIED POLYURETHANE SEALANT

XtraBond™ 9500 is a high performance, one component, permanently flexible, easy to use, multi-purpose fast cure modified polyurethane sealant. XtraBond™ 9500 cures rapidly when exposed to atmospheric moisture to form a durable bond.

### Features

- Non-Yellowing
- Environmentally friendly
- No Solvents, Very Low VOCs
- Can Be Painted in 2 hours
- Fast Cure at a wide range of temperatures
- Aggressive adhesion to common industrial substrates

### Applications

- Transportation Industry
- Cargo Trailer Market
- OEM Applications
- Heating & Cooling Markets
- Sheet Metal Applications
- Metal Building

### Specifications

Skin Time .....	Less than 20 minutes @ 77 degF/ 50% RH
Tack Free Time .....	Less than 1 hour @ 77 degF / 50% RH
Cure Rate .....	1/4" Bead per 24 Hrs
VOC .....	9 g/L (0.0751 lb/gal)
Elongation @ Break .....	450%
Shore A .....	35 +/- 5
Movement Capability % .....	25%
UV Rating .....	No discoloration or change in appearance after 2500 hours of UV
Lap Shear .....	325 psi
Tensile Strength .....	250 psi
Staining .....	None
Low Temp. Flexibility .....	Retained to -90 degrees
High Temp. Flexibility .....	Up to 425 deg. F. for short periods
Sag .....	None



**866-512-GLUE**  
**www.xtrabond.com**

# XTRABOND™ 9500

## MODIFIED POLYURETHANE SEALANT

### HOW TO USE:

For best results, prepare clean, dry surface. Cut nozzle to desired bead size and puncture inner seal. Apply with a caulking gun forcing sealant onto the substrate, then tool if needed. Can be painted within 2 hours depending upon bead size. Clean excess material with mineral spirits or similar solvents. It is the user's responsibility to thoroughly test any proposed uses with any and/or all substrates.

### SURFACE PREPARATIONS:


The substrate must be clean, dry, frost free, sound and free of any oils, greases or incompatible sealers, paints or coatings that may interfere with adhesion. Do not apply if surface is damp or contaminated. It is recommended to test all substrates prior to applications.

### COLORS:

WHITE, ULTRA CLEAR, BEIGE, ALMOND, BRONZE, DESERT TAN, SANDLEWOOD, CANVAS, TERROTONE, SANDSTONE, OFF-WHITE, Special colors upon request

### PACKAGING:

10.1 fl oz plastic fixed nozzle cartridges  
10.3 oz & 20 oz fl oz. Sausages  
1, 3, 5 & 55 gallon available upon request.



### STORAGE LIFE:

10 month shelf life. Material is to be stored in a controlled environment below 75 deg. F.

### SPECIFICATIONS:

ASTM C-920 Type S & TTS-0230C, Grade NT, Class 25

### LIMITED LIFETIME WARRANTY

This product is guaranteed to give satisfactory performance if applied in accordance with the label directions. Liability to Premier Industrial Supply, Inc. (Premier) is limited to a full refund of the purchase price or product replacement if product is proven defective. Premier shall not be liable for loss or damage, whether direct, consequential or incidental. There are no other warranties expressed or implied including the implied warranty of merchantability or fitness for a particular purpose.

### WARNING:

This product contains chemicals known to the state of California to cause cancer, birth defects and/or reproductive harm.



**PREMIER**  
INDUSTRIAL SUPPLY  
www.premierindustrial.net

**866-512-GLUE**  
www.xtrabond.com

REV. 1/07 • SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

distributed by: