

XTRAFoAM™ BLACK

MINIMAL EXPANDING BLACK FOAM SEALANT

XtraFoam™ Black Low Expansion Foam is a very low expanding, one-component, multipurpose, polyurethane foam specially formulated to blend in and seal around voids for the RV industry, transportation industry, HVAC and Automotive industry. The low pressure, airtight insulation foam blocks drafts, moisture and insects without bowing the joints. It is environmentally safe, contains no CFC's or HCFC's and does not require painting when used in the above application.

FEATURES

- Low Expansion Formula
- Black Color
- Excellent stability
- Provides water-resistant, airtight seal
- Excellent adhesion to various substrates
- High thermal and acoustical resistance

APPLICATIONS

- RV & Transportation Industries
- Landscaping
- Insulation
- Pipes
- Electrical Panels
- Areas of air infiltration

SPECIFICATIONS

Base	Polyurethane
Curing System	Moisture Cure
Core Density.....	1.25 -1.70 lbs./ cu.ft.
R-Value ASTM C518	4.25 per inch
Pressure Build	0.15-1.20 psig
Color	Black
Service Temp.....	230 Degrees F
Curing Rate	30 Minutes for a 1/2 bead
Take Free.....	5 minutes for a 1/2 bead
Shelf Life	12 months, from date of mfg.



Proud Member

866-512-GLUE
WWW.PREMIERINDUSTRIAL.NET



PREMIER
INDUSTRIAL SUPPLY

XTRAFOAM™ BLACK

MINIMAL EXPANDING BLACK FOAM SEALANT

APPLICATION:

Type: ALL substrates except PE, PP. State of Surface: clean, free of dust and grease. Preparation: Moistening of the surfaces improves adhesion, curing and denser cellular structure.

Follow Directions on attaching Foam Gun Applicator. For excellent adhesion, do not allow more than 8 minutes to elapse between applying adhesive and attaching substrate. Longer than eight minutes 'open time' will negatively affect adhesion. After following instructions for set-up, the dispensing gun is ready to use.

USAGE:

	LINEAR FEET									
	4,000	5,000	6,000	7,000	8,000	9,000	10,000	11,000	12,000	13,000
1/4" (6.3 mm)	1	2	2	2	2	3	3	4	4	4
3/8" (9.5 mm)	3	4	4	5	6	6	7	8	8	9
1/2" (12.7 mm)	5	6	7	9	10	11	12	13	14	15
	1219	1524	1829	2134	2438	2743	3048	3353	3638	3962

LINEAR METERS

PACKAGING:


20oz spray can. 12 cans per case.

SHELF-LIFE:

12 months in unopened packaging in a cool and dry storage place at temperatures of 75 deg. F. Please note that XtraFoam must be stored in the upright position.

HEALTH AND SAFETY RECOMMENDATION:

Apply the standard industrial hygiene techniques. Wear gloves and safety goggles. Remove cured foam by mechanical means only, never burn away. SEE INDIVIDUAL CANS OF FOAM FOR SPECIFIC INSTRUCTIONS.



DOT 2Q

LIMITED LIFETIME WARRANTY

This product is guaranteed to give satisfactory performance if applied in accordance with the label directions. Liability to Premier Industrial Supply, Inc. (Premier) is limited to a full refund of the purchase price or product replacement if product is proven defective. Premier shall not be liable for loss or damage, whether direct, consequential or incidental. There are no other warranties expressed or implied including the implied warranty of merchantability or fitness for a particular purpose.



REV. 2/09 SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

866-512-GLUE
www.xtrabond.com

distributed by:

