

# XTRAFoAM™ HH

## H A N D H E L D A D H E S I V E F O A M

XtraFoam™ Hand Held Straw Foam is a very low expanding, one-component, multipurpose, polyurethane foam specially formulated to seal around window, doors, insulation areas and where air infiltration occurs. The low pressure, airtight insulation foam blocks drafts, moisture and insects without bowing the windows. It is environmentally safe, contains no CFC's or HCFC's.

### FEATURES

- Low Expansion Formula
- Straw Foam
- Excellent stability (no shrink or post expansion)
- Very good filling capacities
- Provides water-resistant, airtight seal
- Excellent adhesion to various substrates
- High thermal and acoustical resistance

### APPLICATIONS

- Windows & Doors
- Insulation
- Pipes
- Electrical Panels
- Areas of air infiltration



### SPECIFICATIONS

Base .....	Polyurethane
Curing System .....	Moisture Cure
Core Density.....	1.25 -1.70 lbs./ cu.ft.
R-Value ASTM C518 .....	4.25 per inch
Pressure Build .....	0.15-1.20 psi
Color .....	Yellow
Service Temp.....	230 Degrees F
Curing Rate .....	30 Minutes for a 1/2 bead
Take Free.....	5-10 minutes for a 1/2 bead
Shelf Life .....	12 months, from date of mfg.



Proud Member

# 866-512-GLUE

WWW.PREMIERINDUSTRIAL.NET



PREMIER  
INDUSTRIAL SUPPLY

# XTRAF OAM™

## H A N D H E L D A D H E S I V E F O A M

### APPLICATION:

Type: ALL substrates except PE, PP. State of Surface: clean, free of dust and grease. Preparation: Moistening of the surfaces improves adhesion, curing and denser cellular structure.

Be sure to follow directions for can & straw insert. The foam sealant flow can be controlled by tilting the one piece straw adapter with the valve pointing downwards. By activating the adapter lever carefully, the flow rate can be controlled. Foam application can be halted when needed, as shown in the instructions.

### USAGE:

	LINEAR FEET									
	4,000	5,000	6,000	7,000	8,000	9,000	10,000	11,000	12,000	13,000
1/4" (6.3 mm)	2	2	2	2	2	3	3	4	4	4
3/8" (9.5 mm)	3	4	4	5	6	6	7	8	8	9
1/2" (12.7 mm)	5	6	7	9	10	11	12	13	14	15
	1219	1524	1829	2134	2438	2743	3048	3353	3638	3962

### LINEAR METERS

### PACKAGING:


12oz Aerosol Can. 12 cans per case.

### SHELF-LIFE:

12 months in unopened packaging in a cool and dry storage place at temperatures of 75 deg. F. Please note that XtraFoam must be stored in the upright position.

### HEALTH AND SAFETY RECOMMENDATION:

Apply the standard industrial hygiene techniques. Wear gloves and safety goggles. Remove cured foam by mechanical means only, never burn away. SEE INDIVIDUAL CANS OF FOAM FOR SPECIFIC INSTRUCTIONS.



DOT 2Q

### LIMITED LIFETIME WARRANTY

This product is guaranteed to give satisfactory performance if applied in accordance with the label directions. Liability to Premier Industrial Supply, Inc. (Premier) is limited to a full refund of the purchase price or product replacement if product is proven defective. Premier shall not be liable for loss or damage, whether direct, consequential or incidental. There are no other warranties expressed or implied including the implied warranty of merchantability or fitness for a particular purpose.



**866-512-GLUE**  
**www.xtrabond.com**

REV. 2/09 SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

distributed by:

