

XTRAFoAM™ MB

MULTI-BOND ADHESIVE FOAM

XtraFoam™ Adhesive Gun Grade Foam is a multiple purpose one component gun grade foam. It is specially designed for subfloor, marble, drywall, insulation panels and metals. It has extremely low post expansion and adheres well to all building materials such as wood, concrete, brick, marble, granite.

FEATURES

- Low Expansion Formula
- High Bond
- Excellent stability
- Low Post Expansion
- For professional gun applications
- Excellent adhesion to various substrates
- Cold Temperature Application
- Reduce Caulk Use

APPLICATIONS

- Subfloor
- Drywall
- Countertop Applications
- Panels
- Fixing and Sealing Building Materials
- Fastener Applications

SPECIFICATIONS

Base	Polyurethane
Curing System	Moisture Cure
Core Density.....	1.25 -1.70 lbs./ cu.ft.
R-Value ASTM C518	4.25 per inch
Pressure Build	0.15-1.20 psi
Color	Yellow
Service Temp.....	230 Degrees F
Curing Rate	30 Minutes for a 1/2 bead
Take Free.....	8-10 minutes for a 1/2 bead
Shelf Life	12 months, from date of mfg.



Proud Member

866-512-GLUE
WWW.PREMIERINDUSTRIAL.NET



PREMIER
INDUSTRIAL SUPPLY

XTRAFoam™ MB

MULTI-BOND ADHESIVE FOAM

APPLICATION:

Type: ALL substrates except PE, PP. State of Surface: clean, free of dust and grease. Preparation: Moistening of the surfaces improves adhesion, curing and denser cellular structure.

Follow Directions on attaching Foam Gun Applicator. For excellent adhesion, do not allow more than 8 minutes to elapse between applying adhesive and attaching substrate. Longer than eight minutes 'open time' will negatively affect adhesion. After following instructions for set-up, the dispensing gun is ready to use.

USAGE:

COVERAGE COMPARISON									
ESTIMATED USAGE					COVERAGE PER UNIT				
LINEAR FEET*	1,500	3,000	4,500	6,000	7,500	PRODUCT	10oz Cartridge	20oz Cartridge	28oz Quart
XtraFoam (20oz Cartridge)	1	2	3	4	5	XtraFoam	N/A	1500 ft.*	N/A
Adhesive (10oz Cartridge)	45	90	135	180	225	Adhesive	33 ft.*	N/A	88 ft.*
Adhesive (28oz Qt.)	17	34	51	68	85				

*Coverage is calculated using 1/4" bead.
All product information obtained from Liquid Nail® spec data sheet.

PACKAGING:


20oz spray can. 12 cans per case.

SHELF-LIFE:

12 months in unopened packaging in a cool and dry storage place at temperatures of 75 deg. F. Please note that XtraFoam must be stored in the upright position.

HEALTH AND SAFETY RECOMMENDATION:

Apply the standard industrial hygiene techniques. Wear gloves and safety goggles. Remove cured foam by mechanical means only, never burn away. SEE INDIVIDUAL CANS OF FOAM FOR SPECIFIC INSTRUCTIONS.



DOT 2Q

LIMITED LIFETIME WARRANTY

This product is guaranteed to give satisfactory performance if applied in accordance with the label directions. Liability to Premier Industrial Supply, Inc. (Premier) is limited to a full refund of the purchase price or product replacement if product is proven defective. Premier shall not be liable for loss or damage, whether direct, consequential or incidental. There are no other warranties expressed or implied including the implied warranty of merchantability or fitness for a particular purpose.



866-512-GLUE
www.xtrabond.com

REV. 2/09 SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

distributed by:

