

XTRAPATCH™ 75

TEXTURED PATCH SEALANT

XtraPatch™ 75 is a textured, gun grade, acrylic urethane latex patch sealant used for sealing and patching exteriors surfaces. Specially formulated for substrates such as Stucco, Concrete, Masonry and Block Walls. It has excellent adhesion to wood, metal, plastic or glass. XtraPatch™ 75 will not sag, stain or discolor over time.

FEATURES

- Textured Appearance
- Non Sag
- Paintable
- Low Solvents
- VOC Compliant

APPLICATIONS

- Stucco Patch & Repair
- Concrete Patch
- Masonry Applications
- Block Walls

SPECIFICATIONS

Weight per Gallon	8.6 lbs
Toolability	Very good
% Solids	47% (+/-1%)
Type of Cure	Water evaporation (air dry)
Tensile Strength	50 psi
Elongation	200%
Recovery	90%
Adhesion to Wood, Metal & Concrete	Very Good
Odor	Mild
Dry to Touch	30-60 min
Cure Time	3 to 7 days
Freeze-Thaw Stability	Passes 5 cycles



866-512-GLUE
WWW.PREMIERINDUSTRIAL.NET



XTRAPATCH™ 75

TEXTURED LATEX PATCH SEALANT

SURFACE PREPARATION:

Surfaces must be clean and free of grease, oil, loose particles, and chalky material. XtraPatch 75 may be applied with a brush, putty knife, or trowel.

APPLICATION:

XtraPatch 75 may be applied to a damp surface and painted within 30 minutes with vinyl or acrylic latex paint. If oil or alkyd paints are used, patched surface must be completely dry before painting. All-purpose tinting colors can be mixed if desired. To bridge cracks or voids larger than 1/4" deep and 1/4" wide, and less than 1/2" deep by 1/2" wide, fiberglass or polyester reinforcing mesh should be used. Brush or trowel a thin coat around damaged area and allow to become "tacky" before applying mesh. Next brush or trowel on a finish coat, making sure fiberglass mesh is completely covered and free of pinhole.

COLOR:

Flat White

PACKAGING:

10.1 fl oz plastic fixed nozzle cartridges;
29 oz Quarts, 1 gallon pails, 5 gallon pails.

SHELF-LIFE:

12 months shelf life. Material is to be stored in a controlled environment below 75 degrees.

XTRABOND

SEALANTS AND ADHESIVES

LIMITED LIFETIME WARRANTY

This product is guaranteed to give satisfactory performance if applied in accordance with the label directions. Liability to Premier Industrial Supply, Inc. (Premier) is limited to a full refund of the purchase price or product replacement if product is proven defective. Premier shall not be liable for loss or damage, whether direct, consequential or incidental. There are no other warranties expressed or implied including the implied warranty of merchantability or fitness for a particular purpose.



PREMIER
INDUSTRIAL SUPPLY
www.premierindustrial.net

866-512-GLUE
www.xtrabond.com

REV. 2/09 SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

distributed by: