

XTRASTOP™ 550

INTUMESCENT FIRE AND DRAFT SEALANT

XtraStop™ 550 is designed for filling areas around wires, vents, pipes, ducts and other wall penetrations & construction voids. It is a commercial quality, intumescent, non combustibile fire, smoke and draft stopping sealant. XtraStop™ 550 is a water based sealant and can be used wherever ASTM E-814 Specification is needed. The Fire Stop Caulk can withstand 3000 degrees for up to 8 hours and can be safely removed with soap and water prior to curing.

FEATURES

- Non Combustible
- Water Resistant
- Bonds to most Materials
- Non-Sag
- Withstand 3000 Degrees
- Non Toxic
- ASTM E-814 - 8 hours

APPLICATIONS

- Masonry Applications
- High Heat Applications
- HVAC
- Light Commercial Applications
- Chimneys
- Plumbing & Electrical

**3,000 DEG
FORMULA**

SPECIFICATIONS

Color.....	Brick Red
Curing Rate	72 Hours @ 77 deg F/ 50% RH
Shrinkage	+/- 5%
Application Temp.	40 degrees
Viscosity	Spreadable Paste
UV Rating	No discoloration or change in appearance



TOLL-FREE **866-512-GLUE** (4583)
WWW.PREMIERINDUSTRIAL.NET



XTRASTOPTM 550

INTUMESCENT FIRE AND DRAFT SEALANT

APPLICATION:

For best results, prepare clean, dry surface. Cut nozzle desired bead size and puncture inner seal. Apply with a caulking gun forcing sealant onto the substrate, then tool if needed. Can be painted within 2 hours depending upon bead size (Clean excess material with soap and water). It is the user's responsibility to thoroughly test the proposed use of our products with any and all substrates.

COLOR:

Brick Red

PACKAGING:

10.1 fl oz plastic fixed nozzle cartridges;
1, 3, 5 & 55 gallon available upon request.

SHELF-LIFE:


12 months shelf life. XtraStopTM 550 is not affected by freeze thaw but should be stored between freezing and 160° F.

SPECIFICATIONS:

ASTM E-814, ASTM E-119, ASTM-E136, ASTM-E84, ANSI A2.1, AFPA 25.1, UBC 43-1

CERTIFICATION:

XtraStopTM 550 has been factory tested at 3000° F for 8 hours and has been classified by UL as a non-combustible product in compliance with zero flame and zero smoke.



XTRABOND
SEALANTS AND ADHESIVES

LIMITED LIFETIME WARRANTY

This product is guaranteed to give satisfactory performance if applied in accordance with the label directions. Liability to Premier Industrial Supply, Inc. (Premier) is limited to a full refund of the purchase price or product replacement if product is proven defective. Premier shall not be liable for loss or damage, whether direct, consequential or incidental. There are no other warranties expressed or implied including the implied warranty of merchantability or fitness for a particular purpose.



866-512-GLUE
www.xtrabond.com

distributed by: